



*Both sides of form
to be completed.*

❖ REROOF INSPECTION AND SELF-CERTIFICATION FORM ❖

ATTENTION HOMEOWNER:

The Reroof Inspection and Self-Certification Program was created to reduce reroof permit costs and also to expedite the reroofing process. Only Roofing Contractors who are registered as City of Riverside Deputy Reroof Inspectors are authorized to self-inspect the reroof work performed under this permit. Please retain your copy of this document as evidence of inspection approval and contractor self-certification that the work performed met all applicable codes and regulations.

Project Address: _____ **Building Permit Number:** _____

DEPUTY REROOF INSPECTOR AND SELF-CERTIFICATION DECLARATION

1. The reroofed structure is a single-family dwelling or structure accessory to the dwelling.
2. The new roofing was asphalt shingle, hot mop, or roll roofing and was installed in full compliance with all manufacturers' installation instructions and all applicable code requirements.
3. The existing roofing material was asphalt shingle, hot mop, or roll roofing with a maximum of one existing layer of roofing for a combined total of two layers of roofing material (one existing and one new) or remove all original roofing materials down to the roof sheathing.
4. Any necessary replacement sheathing (due to deterioration of existing sheathing) was limited to a maximum of 10% of the total roof area.
5. No structural modifications of the roof framing or roof structure were involved.
6. The required Smoke and Carbon Monoxide retrofit alarms have been installed and tested and the required Smoke and Carbon Monoxide Alarm Retrofit Verification Form has been signed by the property owner.
7. Copies of this signed Reroof Inspection and Self-Certification Form and the Smoke and Carbon Monoxide Alarm Retrofit and Water Efficient Plumbing Fixture Retrofit Verification Form will be given to the property owner and to the City of Riverside Building and Safety Division.

By my signature, I certify that I have personally observed and verified compliance with all 7 items noted above for this reroof project and that I have complied with all codes, ordinances, installation standards, and laws applicable thereto.

Signature of Contractor/Deputy Reroof Inspector

Deputy Inspector ID#

Date

❖ SELF-CERTIFICATION & VERIFICATION FORM ❖
-SMOKE AND CARBON MONOXIDE ALARM RETROFIT
-WATER EFFICIENT PLUMBING FIXTURE RETROFIT

I, _____, owner of the dwelling located at: _____,
(Print Property Owner=s Name) *(Print Address)*

verify that the smoke and carbon monoxide (CO) alarms required by the California Residential Code (CRC) have been installed in the dwelling, in compliance with the CRC and with the manufacturer's instructions and further that they have been tested and do function properly. These alarms enhance life safety within dwellings. CRC Section R314 and R315 require the retrofit of these alarms in existing dwellings when alterations, repairs or additions requiring a permit with a valuation exceeding \$1,000 are made. Generally, the alarms must be hard wired (110 volt) with battery back-up and all alarms are to be interconnected. If the installation of the alarms will require the removal of wall or ceiling finishes or there is no access by means of attic, basement or crawl space, then alarms may be solely battery operated and not interconnected but such battery-only type smoke alarms must be equipped with a 10 year battery and have a silence feature. Alarms must be installed in **all** the following locations within the existing dwelling and must be no more than 10 years old (from the date of manufacture as marked on the unit – units without a date of manufacture identified must be replaced):

- In all bedrooms (*only require Smoke Alarms*)
- Immediately outside and in the immediate vicinity of each bedroom area (*require Smoke and CO Alarms*)
- In each story level, including basements and habitable attics (*require Smoke and CO Alarms*)

For dwellings constructed prior to January 1, 1994, I (the property owner) also verify that all plumbing fixtures within the dwelling unit are in compliance with the applicable retrofit provisions of California Civil Code Section 1101, which requires that the following fixtures do not exceed the flow rates stated:

- Toilets – not more than 1.6 gallon of water per flush
- Urinals – not more than 1 gallon of water per flush
- Showerheads – not more than 2.5 gallons of water per minute
- Faucets – not more than 2.2 gallons of water per minute

I have read and understand the above requirements and affirm by my signature, that all required alarms mentioned above have been properly installed and tested and that the plumbing fixtures mentioned above are in compliance with the applicable water conservation requirements of California Civil Code Section 1101.

Signature of Property Owner

Date

ATTENTION PROPERTY OWNER:

This is a voluntary self-certification verification procedure. If you prefer a City Building Inspector to perform the verification, you must arrange to have an adult present at the time of inspection and provide a ladder and access to locations of all alarms and plumbing fixtures.