



FACE PLATE AND ANCHORS—  
ALHAMBRA FOUNDRY A-3911  
OR EQUAL APPROVED BY CITY

ADJUSTING NUTS TO BE  
TIGHTENED AND SECURED  
IN PLACE WHEN STEEL PLATE  
ANGLE IS IN PROPER POSITION.

PROTECTION BAR

SUPPORT BOLT— ALHAMBRA  
FOUNDRY A-1572  
OR EQUAL APPROVED BY CITY

WELD TO CENTER SUPPORT  
ASSEMBLY(S) FOR CATCH  
BASIN 406.

1. Face plate shall be embedded 4" in adjacent curb on each side of opening.
2. Protection bar shall be 1" diameter plain steel. Embed 5" at each end. Center in opening when support bolts are not used.
3. Support bolts are required if width of opening exceeds 5'. Maximum spacing of bolts is 4'.
4. All exposed metal parts shall be galvanized.

APPROVED BY  
*[Signature]*  
CITY ENGINEER

5/18/11  
DATE

CITY OF RIVERSIDE  
PUBLIC WORKS DEPARTMENT

| MARK | REVISIONS | APPR. | DATE |
|------|-----------|-------|------|
|      |           |       |      |
|      |           |       |      |
|      |           |       |      |

CATCH BASIN INLET

STANDARD DRAWING NO. 402

Sheet 1 of 1