

Approved Reduced Pressure Principle Assemblies (RP)

The backflow assemblies listed here are approved for use as **DOMESTIC SERVICE PROTECTION**. An RP is the minimum level of protection allowable for your application.

The devices listed below have been classified by the recognized testing organization (USC) as $\leq 0.25\%Pb$ and are currently acceptable for domestic applications.

AMES

Model	Size	Model	Size
4000SS	2 ½, 3, 4, 6	Colt 400Z	2 ½, 3, 4
Colt 400	2 ½, 3, 4, 6, 8, 10	Maxim 400	2 ½, 3, 4, 6, 8, 10
Colt 400BF	4, 6	Maxim 400N	2 ½, 3
Colt 400N	2 ½, 3, 4	Maxim 400Z	2 ½, 3

ARI

Model	Size		
RP500	¾, 1		

FEBCO

Model	Size	Model	Size
760	2 ½, 3, 4, 6, 8, 10	LF825Y	¾, 1, 1 ½, 2
760N	2 ½, 3, 4	LF825YA	¾, 1, 1 ½, 2
760Z	2 ½, 3, 4	LF860	½, ¾, 1, 1 ¼, 1 ½, 2

FLOMATIC

Model	Size	Model	Size
RPZ	4, 6	RPZE II	½, ¾
RPZE	¾, 1, 1 ½, 2		

WATTS

Model	Size	Model	Size
957	2 ½, 3, 4, 6, 8, 10	LF009QT	½
957BF	4, 6	LF909	2 ½, 3
957N	2 ½, 3, 4	LF909M1	8, 10
957NQT	2 ½, 3, 4	LF909M1QT	1 ¼, 1 ½, 2
957QT	2 ½, 3, 4	LF909QT	¾, 1
957Z	2 ½, 3, 4	LF919AQT	¾, 1, 1 ¼, 1 ½, 2
957ZQT	2 ½, 3, 4	LF919QT	¾, 1, 1 ¼, 1 ½, 2
LF009	2 ½, 3	LFU919AQT	¾, 1, 1 ¼, 1 ½, 2
LF009M2QT	1, 1 ¼, 1 ½, 2	LFU919QT	¾, 1, 1 ¼, 1 ½, 2
LF009M3QT	¾	SS009M3QT	¼, 3/8, ½, ¾

WILKINS

Model	Size	Model	Size
375	2 ½, 3, 4, 6, 8, 10	475MS	2 ½, 3, 4, 6, 8, 10
375A	2 ½, 3, 4, 6, 8, 10	475V	2 ½, 3, 4, 6, 8, 10
375AR	2 ½, 3, 4, 6, 8, 10	475VMS	2 ½, 3, 4, 6, 8, 10
375ARXL	2 ½, 3, 4, 6, 8, 10	475XL	2 ½, 3, 4, 6, 8, 10
375AXL	2 ½, 3, 4, 6, 8, 10	475XLMS	2 ½, 3, 4, 6, 8, 10
375MS	2 ½, 3, 4, 6, 8, 10	475XLV	2 ½, 3, 4, 6, 8, 10
375XL	½, ¾, 1, 1 ¼, 1 ½, 2, 2 ½, 3, 4, 6, 8, 10	475XLVMS	2 ½, 3, 4, 6, 8, 10
375XLMS	2 ½, 3, 4, 6, 8, 10	975XL2	¼, 3/8, ½, ¾, 1, 1 ¼, 1 ½, 2
475	2 ½, 3, 4, 6, 8, 10	975XLST	3/8, ½

RP devices not listed must be approved by the California Department of Public Health as described within Title 17 Section 7601 and conform to the provisions set forth within the California Health and Safety Code Section 116875-116880.